





## RGB48/NX G5 07W

RGB LED strips



<b>LIGHT TYPE</b>	RGB
<b>LEDs/M</b>	48 LEDs/m
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>PHOTOMETRIC</b>	120° beam angle
<b>LUMINOUS FLUX</b>	Total: 316 Lm/m (96 Lm/ft) Red: 65 Lm/m (20 Lm/ft) Green: 208 Lm/m (63 Lm/ft) Blue: 43 Lm/m (13 Lm/ft)
<b>EFFICACY</b>	44 Lm/W
<b>LIFETIME</b>	L90B10 60.000 h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>VOLTAGE</b>	24 VDC
<b>WATTAGE</b>	7.2 W/m   2.19 W/ft

<b>CUTTING STEP</b>	125 mm (4.92")
<b>MAX RUN</b>	9 m (30')
<b>PACKING</b>	10 m, 50 m or customized length per reel
<b>DIMENSIONS</b>	Width: 10 mm Height: 1.58 mm (0.06")

<b>TEMPERATURE</b>	Tc max <75°C ( 167°F )
<b>OPERATING TEMP.</b>	-25°C...+50°C ( -13°F...122°F )



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.