


TW2-112/NX G4 048W 827/865

Tunable white LED strips



LIGHT TYPE	Tunable white Dual
LEDs/M	112 LEDs/m
CCT	Warm: 2700K Cold: 6500K
CRI	Warm: 80+ Cold: 80+
COLOR CONSISTENCY	3-Step MacAdam
PHOTOMETRIC	120° beam angle
LUMINOUS FLUX	6462 Lm/m (1970 Lm/ft)
EFFICACY	135 Lm/W
LIFETIME	L90B10 60.000 h

CONTROL	Dimmable
----------------	----------

VOLTAGE	24 VDC
WATTAGE	48.0 W/m 14.63 W/ft

CUTTING STEP	62.5 mm (2.46")
MAX RUN	3.5 m (11')
PACKING	10 m, 50 m or customized length per reel
DIMENSIONS	Width: 8 mm Height: 1.62 mm (0.06")

TEMPERATURE	T _c max <75°C (167°F)
OPERATING TEMP.	-25°C...+50°C (-13°F...122°F)



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.