



# ULA L

ULaL A1112 IBC PBK OPL / RGB48/Nx G5 07W L1000



<b>TYPE</b>	RGB
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 164 Lm Light Source: 316 Lm Red: 34 Lm Green: 108 Lm Blue: 22 Lm
<b>EFFICACY</b>	Luminaire: 23 Lm/W
<b>LIFETIME</b>	Light Source: 44 Lm/W L90B10 60.000h
<b>CONTROL</b>	Dimmable
<b>LUMINAIRE POWER</b>	7.2 W
<b>INPUT VOLTAGE</b>	24V DC
<b>COVER</b>	Opal
<b>HOUSING</b>	Extruded aluminum, Black
<b>IP CLASS</b>	IP40 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment
<b>DIMENSIONS</b>	Width: 34 mm / 1.34" Height: 60 mm / 2.36" Length: 1003 mm / 3.3'



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.