



## ULA S IP67

UlaS.IP67 AULSO SBC AGY ECL / RGB48/Nx G5 011W L1000



<b>TYPE</b>	RGB
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 306 Lm Light Source: 480 Lm Red:66 Lm Green:195 Lm Blue:44 Lm
<b>EFFICACY</b>	Luminaire: 27 Lm/W Light Source: 42 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	11.52 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Clear
<b>HOUSING</b>	Extruded aluminum, Grey
<b>IP CLASS</b>	IP67 ingress protection
<b>OTHER DETAILS</b>	Start segment

<b>DIMENSIONS</b>	Width: 16 mm / 0.63" Height: 16 mm / 0.63" Length: 1001.5 mm / 3.3'
-------------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%.  
All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.