





# XLINE

xLine A017M IEC PWE EOP / TW56/Nx G5 09W 820/840 L1000



<b>TYPE</b>	Tunable white
<b>CCT (WARM)</b>	2000K
<b>CRI (WARM)</b>	CRI 80+
<b>CCT (COLD)</b>	4000K
<b>CRI (COLD)</b>	CRI 80+
<b>COLOR CONSISTENCY</b>	3-Step MacAdam
<b>LUMINOUS FLUX</b>	Luminaire: 248 Lm Light Source: 1234 Lm
<b>EFFICACY</b>	Luminaire: 26 Lm/W Light Source: 129 Lm/W
<b>LIFETIME</b>	L90B10 60.000h

<b>CONTROL</b>	Dimmable
----------------	----------

<b>LUMINAIRE POWER</b>	9.6 W
<b>INPUT VOLTAGE</b>	24V DC

<b>COVER</b>	Opal
<b>HOUSING</b>	Extruded aluminum, White
<b>IP CLASS</b>	IP67 ingress protection
<b>OTHER DETAILS</b>	Luminaire segment

<b>DIMENSIONS</b>	Width: 26 mm / 1.02" Height: 25 mm / 0.98" Length: 1004 mm / 3.3'
-------------------	---



Possible allowed deviation of optical and electrical values are ±15%. Allowed measurement uncertainty ±7%. All values in datasheet are for reference only and customers should take these values on their own risk. HOLECTRON reserves the right for changes without prior notice.